



Model	Spec.			Size(mm)	Rated Voltage V	Rated Frequency Hz	Rated Current A	Input Power w	Speed r.p.m	Static Pressure mmAq	Maximum Air Flow m ³ /min	Noise dBA	Safety Approval			Weight g
	A	B	C										UL	CCC	CE	
CE65120A11	120	130	90	110	60	0.31	21	1600	6.0	2.0	40	○		○	1420	
CE65120A22				220	50	0.14	19	1600	6.0	2.0	40	○	○	○		
CE65190A11	190	200	160	110	60	0.30	22	1100	2.6	2.2	43	○		○	1530	
CE65190A22				220	50	0.16	20	1100	2.6	2.2	43	○	○	○		
CE65240A11	242	252	192	110	60	0.65	32	1500	3.8	3.9	45	○		○	1690	
CE65240A22				220	50	0.33	30	1500	3.8	3.9	45	○	○	○		
CE65300A11	303	312	272	110	60	0.68	41	1300	4.2	4.5	45	○		○	1760	
CE65300A22				220	50	0.35	40	1300	4.2	4.5	45	○	○	○		
CE65360A11	362	372	332	110	60	0.91	51	1300	5.0	5.3	47	○		○	1820	
CE65360A22				220	50	0.45	52	1300	5.0	5.3	47	○	○	○		
CE65420A11	422	432	382	110	60	0.99	59	1300	6.3	5.2	50	○		○	1850	
CE65420A22				220	50	0.55	58	1300	6.3	5.2	50	○	○	○		