

C7015 AXIAL SERIES

DC COOLING FAN



SIZE :

70x70x15mm (2.76"x2.76"x0.59")

CONSTRUCTION :

Glass fiber reinforced plastic:
Impeller and housing PBT are UL 94V-0 rating

OPERATING TEMPERATURE :

Ball bearing - 30°C to + 75°C
*Minimum ambient temperature -15°C , admissible for a short time at -30°C ; without reaching dew point.
Sleeve bearing - 10°C to + 60°C

FUNCTION :

auto-restart option
frequency generator signal option

WEIGHT :

45 grams

Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	RATED CURRENT	RATED INPUT POWER	SPEED R.P.M.	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE dB-A
		VDC	A	W		m ³ /min	CFM	mmH ₂ O	IN H ₂ O	
CB701512L	Ball	12	0.13	1.56	2600	0.706	24.95	2.14	0.084	27.8
CS701512L	Sleeve									
CB701512M	Ball	12	0.17	2.04	3200	0.852	30.10	2.93	0.115	32.8
CS701512M	Sleeve									
CB701512H	Ball	12	0.20	2.40	3800	1.048	37.02	4.36	0.171	37.6
CS701512H	Sleeve									
CB701524L	Ball	24	0.08	1.92	2600	0.706	24.96	2.14	0.084	27.8
CS701524L	Sleeve									
CB701524M	Ball	24	0.10	2.40	3200	0.852	30.10	2.93	0.115	32.8
CS701524M	Sleeve									
CB701524H	Ball	24	0.12	2.88	3800	1.048	37.02	4.36	0.171	37.6
CS701524H	Sleeve									

*Long life bearing is available

