



SIZE :

ø72x60mm (2.83"x2.36")

CONSTRUCTION :

- Die-cast aluminum frame
- Shaded pole motor
- Impedance protected

OPERATING TEMPERATURE :

Ball bearing - 30°C to +75°C

*Minimum ambient temperature -15°C , admissible for a short time at -30°C ; without reaching dew point.

Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	FREQUENCY	Rated loading Input	SPEED	No loading Input	Free Running Current	Running Speed	Locked Rotor Input	No Loading Starting Voltage	
		VAC	Hz	W	R.P.M.	W	mA	R.P.M.	W	mA	VAC
CB72115H	Ball	115	50/60	88/76	2800/3200	47/33	460/350	2970/3600	125/115	890/810	34/35
CB72115M	Ball	115	50/60	62/52	2350/2200	39/28	430/320	2965/3570	105/95	730/640	35/36
CB72115L	Ball	115	50/60	45/35	1400/1650	35/26	370/270	2960/3560	95/85	620/460	37/38
CB72230H	Ball	230	50/60	88/76	2800/3200	42/33	260/230	2970/3600	125/115	460/400	65/70
CB72230M	Ball	230	50/60	75/60	2350/2200	39/28	210/170	2960/3560	105/95	380/320	66/71
CB72230L	Ball	230	50/60	45/35	1400/1650	35/26	190/150	2960/3560	95/85	330/260	68/73

Dimensions (mm)

