

C4010 AXIAL SERIES



SIZE :

40x40x10mm (1.57"x1.57"x0.39")

CONSTRUCTION :

Glass fiber reinforced plastic:

Impeller and housing PBT are UL 94V-0 rating

OPERATING TEMPERATURE :

Ball bearing - 30°C to + 75°C

*Minimum ambient temperature -15°C , admissible for a short time at -30°C ; without reaching dew point.

Sleeve bearing - 10°C to + 60°C

FUNCTION :

auto-restart option

frequency generator signal option

WEIGHT :

12.3 grams

Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	RATED CURRENT	RATED INPUT POWER	SPEED R.P.M.	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE dB-A
		VDC	A	W		m³/min	CFM	mmH₂O	IN H₂O	
CB401005L	Ball	5	0.16	0.80	4000	0.137	3.66	0.87	0.034	14.8
CS401005L	Sleeve									
CB401005M	Ball	5	0.19	0.95	5000	0.184	6.49	2.31	0.091	23.8
CS401005M	Sleeve									
CB401005H	Ball	5	0.25	1.25	6000	0.217	7.65	0.87	0.034	14.8
CS401005H	Sleeve									
CB401012L	Ball	12	0.08	0.96	4000	0.137	4.85	1.56	0.061	20.7
CS401012L	Sleeve									
CB401012M	Ball	12	0.12	1.44	5000	0.184	6.49	2.31	0.091	23.8
CS401012M	Sleeve									
CB401012H	Ball	12	0.15	1.80	6000	0.217	7.65	3.43	0.135	28.00
CS401012H	Sleeve									
CB401024M	Ball	24	0.08	1.92	5000	0.184	6.49	2.31	0.091	23.8
CS401024M	Sleeve									
CB401024H	Ball	24	0.10	2.40	6000	0.217	7.65	3.43	0.135	28.0
CS401024H	Sleeve									

*Long life bearing is available

