

## C13538P SERIES



### SIZE :

135\*135\*38mm

### CONSTRUCTION :

- Die-cast aluminum housing
- Glass fiber reinforced plastic:  
Impeller are UL 94V-0 rating
- Impedance protected
- Leader wire or terminal is available

### OPERATING TEMPERATURE :

Ball bearing - 30°C to +75°C

\*Minimum ambient temperature -15°C, admissible for a short time at -30°C ; without reaching dew point.

Sleeve bearing - 10°C to +60°C

### WEIGHT :

650grams

### Specifications

Specifications are subject to change without notice

| MODEL NO.     | BEARING | RATED VOLTAGE | FREQUENCY | MAX. RATED CURRENT | MAX. INPUT POWER | SPEED     | MAX. AIR FLOW | MAX. AIR PRESSURE   | NOISE |
|---------------|---------|---------------|-----------|--------------------|------------------|-----------|---------------|---------------------|-------|
|               |         | VAC           | Hz        | mA                 | W                | R.P.M.    | CFM           | IN H <sub>2</sub> O | dB-A  |
| CB13538-115HP | Ball    | 115           | 50/60     | 340/300            | 25/20            | 2250/2450 | 95/100        | 0.28/0.32           | 55/57 |
| CS13538-115HP | Sleeve  |               |           |                    |                  |           |               |                     |       |
| CB13538-230HP | Ball    | 230           | 50/60     | 180/140            | 25/20            | 2250/2450 | 95/100        | 0.28/0.32           | 55/57 |
| CS13538-230HP | Sleeve  |               |           |                    |                  |           |               |                     |       |

