

## C2510 AXIAL SERIES



### SIZE :

25x25x10mm (0.98"x0.98"x0.39")

### CONSTRUCTION :

Glass fiber reinforced plastic:

Impeller and housing PBT are UL 94V-0 rating

### OPERATING TEMPERATURE :

Ball bearing - 30°C to + 75°C

\*Minimum ambient temperature -15°C , admissible for a short time at -30°C ; without reaching dew point.

Sleeve bearing - 10°C to + 60°C

### FUNCTION :

auto-restart option

frequency generator signal option

### WEIGHT :

5,7 grams

## Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	RATED CURRENT	RATED INPUT POWER	SPEED R.P.M.	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE dB-A
		VDC	A	W		m³/min	CFM	mmH₂O	IN H₂O	
CB251005L	Ball	5	0.16	0.80	7000	0.044	1.55	2.79	0.110	20.6
CS251005L	Sleeve									
CB251005M	Ball	5	0.19	0.95	10000	0.068	2.40	4.32	0.170	24.9
CS251005M	Sleeve									
CB251005H	Ball	5	0.25	1.25	13000	0.090	3.19	6.35	0.250	30.9
CS251005H	Sleeve									
CB251012L	Ball	12	0.08	0.96	7000	0.044	1.55	2.79	0.110	20.6
CS251012L	Sleeve									
CB251012M	Ball	12	0.11	0.32	10000	0.068	2.40	4.32	0.170	24.9
CS251012M	Sleeve									
CB251012H	Ball	12	0.15	1.80	13000	0.090	3.19	6.35	0.250	30.9
CS251012H	Sleeve									

\*Long life bearing is available

