

C11025P SERIES



SIZE :

110x110x25mm (4.33"x4.33"x0.98")

CONSTRUCTION :

- Die-cast aluminum housing
- Glass fiber reinforced plastic:
Impeller are UL 94V-0 rating
- Impedance protected
- Leader wire or Terminal is available

OPERATING TEMPERATURE :

Ball bearing - 30°C to +75°C

*Minimum ambient temperature -15°C , admissible for a short time at -30°C ; without reaching dew point.

Sleeve bearing - 10°C to +60°C

WEIGHT :

310 grams

Specifications

Specifications are subject to change without notice

| MODEL NO. | BEARING | RATED VOLTAGE | FREQUENCY | MAX. RATED CURRENT | MAX. INPUT POWER | SPEED | MAX. AIR FLOW | | MAX. AIR PRESSURE | | NOISE |
|---------------|---------|---------------|-----------|--------------------|------------------|-----------|---------------------|-------|--------------------|---------------------|-------|
| | | VAC | Hz | mA | W | R.P.M. | m ³ /min | CFM | mmH ₂ O | IN H ₂ O | |
| CB11025-115HP | Ball | 115 | 50/60 | 190/180 | 19/18 | 2200/2400 | 1.70/2.01 | 60/71 | 1.70/2.01 | 0.07/0.08 | 36/38 |
| CS11025-115HP | Sleeve | | | | | | | | | | |
| CB11025-230HP | Ball | 230 | 50/60 | 90/90 | 19/18 | 2200/2400 | 1.70/2.01 | 60/71 | 1.70/2.01 | 0.07/0.08 | 36/38 |
| CS11025-230HP | Sleeve | | | | | | | | | | |

