



SIZE :

120x120x25mm (4.72"x4.72"x0.98")

CONSTRUCTION :

- Die-cast aluminum housing
- Glass fiber reinforced plastic:
Impeller are UL 94V-0 rating
- Impedance protected
- Leader wire or Terminal is available

OPERATING TEMPERATURE :

Ball bearing - 30°C to +75°C

*Minimum ambient temperature -15°C , admissible for a short time at -30°C ; without reaching dew point.

Sleeve bearing - 10°C to +60°C

WEIGHT :

330 grams

Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	FREQUENCY	MAX. RATED CURRENT	MAX. INPUT POWER	SPEED R.P.M.	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE dB-A
		VAC	Hz	mA	W		m ³ /min	CFM	mmH ₂ O	IN H ₂ O	
CB12025-115HP	Ball	115	50/60	170/150	16/14	2000/2400	1.61/1.86	56.72/65.57	2.64/2.43	0.10/0.09	39/42
CS12025-115HP	Sleeve										
CB12025-230HP	Ball	230	50/60	95/85	18/16	2000/2400	1.61/1.86	56.72/65.57	2.64/2.43	0.10/0.09	39/42
CS12025-230HP	Sleeve										

