



Model	Spec.	Size(mm)			Rated Voltage V	Rated Frequency Hz	Rated Current A	Input Power w	Speed r.p.m	Static Pressure mmAq	Maximum Air Flow m ³ /min	Noise dBA	Safety Approval			Weight g
		A	B	C									UL	CCC	CE	
CE60090A11		98	110	68	110	60	0.31	23	2550	6.2	1.9	43	○		○	1200
CE60090A22					220	50	0.15	25	2350	6.0	1.9	43	○	○	○	
CE60180A11		181	193	154	110	60	0.49	41	2300	6.0	3.0	48	○		○	1350
CE60180A22					220	50	0.26	30	2300	6.0	3.0	48	○	○	○	
CE60240A11		242	254	212	110	60	0.60	30	1900	5.2	3.3	47	○		○	1400
CE60240A22					220	50	0.27	32	1900	5.2	3.3	47	○	○	○	
CE60300A11		303	315	273	110	60	0.63	31	2000	5.4	4.7	46	○		○	1500
CE60300A22					220	50	0.32	32	2000	5.4	4.7	46	○	○	○	
CE60350A22		353	365	323	110	60	0.63	37	2000	5.0	4.8	46	○		○	1600
CE60350A22					220	50	0.32	39	2000	5.0	4.8	46	○	○	○	
CE60420A11		418	430	388	110	60	0.68	43	1600	4.6	5.2	45	○		○	1650
CE60420A22					220	50	0.35	42	1800	4.8	5.2	45	○	○	○	