

## C6015 AXIAL SERIES



### SIZE :

60x60x15mm (2.36"x2.36"x0.59")

### CONSTRUCTION :

Glass fiber reinforced plastic:

Impeller and housing PBT are UL 94V-0 rating

### OPERATING TEMPERATURE :

Ball bearing - 30°C to + 75°C

\*Minimum ambient temperature -15°C, admissible for a short time at -30°C ; without reaching dew point.

Sleeve bearing - 10°C to + 60°C

### FUNCTION :

auto-restart option

frequency generator signal option

### WEIGHT :

30.6 grams

## Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	RATED CURRENT	RATED INPUT POWER	SPEED R.P.M.	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE dB-A
		VDC	A	W		m³/min	CFM	mmH₂O	IN H₂O	
CB601505L	Ball	5	0.16	0.78	3000	0.422	14.92	2.43	0.096	24.8
CS601505L	Sleeve									
CB601505M	Ball	5	0.34	1.69	3800	0.551	19.47	4.03	0.159	30.7
CS601505M	Sleeve									
CB601505H	Ball	5	0.47	2.34	4600	0.668	23.58	5.56	0.219	36.1
CS601505H	Sleeve									
CB601512L	Ball	12	0.08	0.94	3000	0.422	14.92	2.43	0.096	24.8
CS601512L	Sleeve									
CB601512M	Ball	12	0.16	1.87	3800	0.551	19.47	4.03	0.159	30.6
CS601512M	Sleeve									
CB601512H	Ball	12	0.23	2.81	4600	0.668	23.58	5.56	0.219	36.1
CS601512H	Sleeve									
CB601524L	Ball	24	0.07	1.56	3000	0.422	14.92	2.43	0.096	24.8
CS601524L	Sleeve									
CB601524M	Ball	24	0.10	2.50	3800	0.551	19.47	4.03	0.159	30.7
CS601524M	Sleeve									
CB601524H	Ball	24	0.14	3.43	4600	0.668	23.58	5.56	0.219	36.1
CS601524H	Sleeve									

\*Long life bearing is available

