

C17251 AXIAL SERIES

DC COOLING FAN



SIZE :

172x150x51mm (6.77"x5.91"x2")

CONSTRUCTION :

Glass fiber reinforced plastic:
Impeller and housing PBT are UL 94V-0 rating

OPERATING TEMPERATURE :

Ball bearing - 30°C to + 75°C
*Minimum ambient temperature -15°C , admissible for a short time at -30°C ; without reaching dew point.
Sleeve bearing - 10°C to + 60°C

FUNCTION :

auto-restart option
frequency generator or rotation detection signal option

WEIGHT :

762.0 grams

Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	RATED CURRENT	RATED INPUT POWER	SPEED R.P.M.	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE dB-A
		VDC	A	W		m³/min	CFM	mmH₂O	IN H₂O	
CB1725112L	Ball	12	2.20	26.40	2600	6.462	228.20	21.55	0.848	48.70
CB1725112M	Ball	12	3.00	36.00	3200	7.953	280.87	32.64	1.285	62.80
CB1725112H	Ball	12	3.50	42.00	4000	10.437	368.60	46.63	1.836	68.30
CB1725124L	Ball	24	0.90	21.60	2600	6.462	228.20	21.55	0.848	45.80
CB1725124M	Ball	24	1.20	28.80	3200	7.953	280.87	32.64	1.285	48.70
CB1725124H	Ball	24	1.60	38.40	4000	10.437	368.60	46.63	1.836	62.80
CB1725148L	Ball	48	0.40	19.20	2600	6.462	228.20	21.55	0.848	45.80
CB1725148M	Ball	48	0.48	23.04	3200	7.953	280.87	32.64	1.285	48.70
CB1725148H	Ball	48	0.75	36.00	4000	10.437	368.60	46.63	1.836	62.80

*Long life bearing is available

