



Model	Spec.	Size(mm)			Rated Voltage V	Rated Frequency Hz	Rated Current A	Input Power w	Speed r.p.m	Static Pressure mmAq	Maximum Air Flow m ³ /min	Noise dBA	Safety Approval			Weight g
		A	B	C									UL	CCC	CE	
CE50090A11		100	110	160	110	60	0.13	9.5	2900	1.0	1.0	34	○		○	580
CE50090A22					220	50	0.08	12	2660	0.8	0.9	33	○	○	○	
CE50150A11		160	170	225	110	60	0.13	10.5	2100	1.2	1.31	36	○		○	620
CE50150A22					220	50	0.08	13	2600	1.4	1.66	38	○	○	○	
CE50190A11		200	210	266	110	60	0.19	15	2600	1.2	1.6	37	○		○	740
CE50190A22					220	50	0.09	13	2500	0.9	1.5	36	○	○	○	
CE50290A11		300	310	375	110	60	0.30	21	2900	2.0	2.7	42	○		○	1000
CE50290A22					220	50	0.14	18.5	2600	1.5	2.6	41	○	○	○	
CE50350A11		362	372	437	110	60	0.29	21	2800	1.7	2.9	39	○		○	1100
CE50350A22					220	50	0.14	19	2550	1.6	2.7	38	○	○	○	
CE50420A11		422	432	497	110	60	0.28	33	1700	1.8	2.25	42	○		○	1220
CE50420A22					220	50	0.24	28	2200	12.0	3.15	45	○	○	○	