

## C8015 AXIAL SERIES



### SIZE :

80x80x15mm (3.15"x3.15"x0.59")

### CONSTRUCTION :

Glass fiber reinforced plastic:  
Impeller and housing PBT are UL 94V-0 rating

### OPERATING TEMPERATURE :

Ball bearing - 30°C to + 75°C

\*Minimum ambient temperature -15°C , admissible for a short time at -30°C ;  
without reaching dew point.

Sleeve bearing - 10°C to + 60°C

### FUNCTION :

auto-restart option  
frequency generator signal option

### WEIGHT :

52.4 grams

## Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	RATED CURRENT	RATED INPUT POWER	SPEED	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE
		VDC	A	W	R.P.M.	m <sup>3</sup> min	CFM	mmH <sub>2</sub> O	IN H <sub>2</sub> O	
CB801512L	Ball	12	0.15	1.80	2500	0.854	30.17	3.01	0.188	31.10
CS801512L	Sleeve									
CB801512M	Ball	12	0.25	3.00	3000	1.025	36.21	4.37	0.172	36.50
CS801512M	Sleeve									
CB801512H	Ball	12	0.50	6.00	4000	1.365	48.22	7.68	0.302	43.70
CS801512H	Sleeve									
CB801524L	Ball	24	0.10	2.40	2500	0.854	30.17	3.01	0.118	31.10
CS801524L	Sleeve									
CB801524M	Ball	24	0.15	3.60	3000	1.025	36.21	4.37	0.172	36.50
CS801524M	Sleeve									
CB801524H	Ball	24	0.25	6.00	3500	1.169	41.29	5.80	0.228	41.20
CS801524H	Sleeve									

\*Long life bearing is available

