



SIZE :

ø59x36mm (2.32"x1.42")

CONSTRUCTION :

- Die-cast aluminum frame
- Shaded pole motor
- Impedance protected

OPERATING TEMPERATURE :

Ball bearing - 30°C to +75°C

*Minimum ambient temperature -15°C , admissible for a short time at -30°C ; without reaching dew point.

Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	FREQUENCY	Rated loading Input	SPEED	No loading Input	Free Running Current	Free Running Speed	Locked Rotor Input	Locked Rotor Current	No Loading Starting Voltage
		VAC	Hz	W	R.P.M.	W	mA	R.P.M.	W	mA	VAC
CB59115H	Ball	115	50/60	21/20	2750/3100	18/15	230/200	2800/3500	27/25	280/250	37/44
CB59115M	Ball	115	50/60	14/13	2400/2500	12/10	160/130	2795/3495	22/18	220/190	39/47
CB59115L	Ball	115	50/60	12/9	1700/1800	10/7	130/110	2790/3490	17/15	180/150	42/50
CB59230H	Ball	230	50/60	21/20	2750/3100	18/15	120/110	2800/3500	27/25	140/130	62/66
CB59230M	Ball	230	50/60	14/13	2400/2500	12/10	80/60	2795/3495	22/18	110/90	64/68
CB59230L	Ball	230	50/60	12/9	1700/1800	10/7	60/50	2790/3490	17/15	90/70	69/72

Dimensions (mm)

