



SIZE :

92x92x38mm (3.62"x3.62"x1.50")

CONSTRUCTION :

- Die-cast aluminum housing
- Glass fiber reinforced plastic:
Impeller are UL 94V-0 rating
- Impedance protected
- Leader wire or terminal is available

OPERATING TEMPERATURE :

Ball bearing - 30°C to +75°C

*Minimum ambient temperature -15°C , admissible for a short time at -30°C ; without reaching dew point.

Sleeve bearing - 10°C to +60°C

WEIGHT :

350 grams

Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	FREQUENCY	MAX. RATED CURRENT	MAX. INPUT POWER	SPEED	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE
		VAC	Hz	mA	W	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	
CB9238-115MP	Ball	115	50/60	130/110	14/12	2200/2400	0.79/0.91	28/32	3.50/4.20	0.14/0.17	27/31
CS9238-115MP	Sleeve										
CB9238-230MP	Ball	230	50/60	90/80	14/12	2200/2400	0.79/0.91	28/32	3.50/4.20	0.14/0.17	27/31
CS9238-230MP	Sleeve										
CB9238-115HP	Ball	115	50/60	160/140	16/14	2400/2900	1.22/1.42	43/50	4.50/5.50	0.18/0.22	32/36
CS9238-115HP	Sleeve										
CB9238-230HP	Ball	230	50/60	120/110	18/16	2400/2900	1.22/1.42	43/50	4.50/5.50	0.18/0.22	32/36
CS9238-230HP	Sleeve										

